

Food Hygiene

### DYCEM CONTAMINATION CONTROL YOU CAN TRUST







Dycem contamination control flooring solutions are manufactured with Biomaster (a silver antimicrobial) as an integral ingredient, providing effective and longlasting antimicrobial protection.

Biomaster is proven to reduce the growth of harmful bacteria such as Campylobacter, MRSA, E.Coli, Listeria, Salmonella and many others by up to 99.9%.

## THE SOLUTION – **HIGH PERFORMANCE** CONTAMINATION CONTROL TECHNOLOGY

The Dycem Cleanzone is the most effective, scientifically proven solution and provides a simple, long lasting and high performance method of minimising foot and wheel borne contamination. In independent tests carried out at GlaxoSmithKline it was proven that Dycem Cleanzones prevent up to **99.9% of all viable and non-viable** foot and wheel borne contamination from entering a critical area.



#### PROTECTION

The most effective solution available, trapping up to 99.9% of foot and wheelborne particulates.



#### SIZE

Dycem allows for a minimum of six foot falls or three wheel rotations, which is required for full decontamination.



#### **PARTICLE RETENTION**

The polymeric surface attracts, collects and retains particles and is easy to clean.



### WHEELED TRAFFIC

The only solution for heavy wheeled traffic areas.

### ENVIRONMENTAL

Dycem CleanZones can be recycled into less critical applications at the end of their life-cycle.

### PERFORMANCE

Dycem performance is maintained even after several overstrikes.



#### FLEXIBLE PAYMENT

Dycem schemes provide controllable and proven lower running costs.



#### AUDITING

Dycem is included in Standard Operating Procedures (SOPs) & meets requirements of regulatory bodies.



### WARRANTY

All products are warrantied for 12 months subject to normal usage wear and tear.

#### Length for heavy traffic loads ••••

### FACT

With every footstep and wheel rotation, contamination gradually builds up in layers.

Length for normal traffic loads




After 4 footfalls or 2 wheel rotations **500%** EFFECTIVE

After 2 footfalls or 1 wheel rotation 25% EFFECTIVE

Multiple steps on Dycem flooring are required to fully decontaminate your feet and wheels. Peel off mats do not have the surface area or ability to allow for multiple footsteps/wheel rotations to guarantee effective decontamination from the built up layers of contamination.

\* Figures shown are 'up to' values based on optimum care and use



### Green/GN

Red/RD

### CLEANZONE For Pedestrian & Light wheeled traffic

Dycem Cleanzone is a high performance contamination control zone suitable for light wheeled traffic and heavier pedestrian flows. Permanently installed, it is the most effective way of controlling all forms of foot, wheel and air borne contamination. Dycem Cleanzone is available in a range of attractive designs which means it still looks good between wet cleaning.

### **OPTIONS**

Cleanzone has the flexibility to be installed into in a variety of different sized and shaped areas, it is accompanied by a number of edging system choices.

### BENEFITS

- Prevents up to 99.9% of contamination from entering your critical area
- Reduced floor and air particle/microbial counts
- Improved yield, cost savings and profitability
- Reduced risk of high product rejection rates
- Dycem products cannot be bypassed and require no overt action
- Available in a range of low profile edging systems
- Coving and inlaid options available

### WORKZONE For large trolleys, pallet trucks & fork lifts


Dycem Workzone has been specially designed to remove contamination from areas subject to heavy wheeled traffic. It effectively attracts, collects and retains contamination from the wheels of forklifts, pallet trucks, large trolleys and carts, preventing particles and microbes from getting into your critical areas.

### **OPTIONS**

Workzone has the flexibility to be installed into in a variety of heavy duty areas, it is accompanied by either a heavy duty aluminium or low profile food grade stainless steel option.

### **BENEFITS**

- Prevents up to 99.9% of contamination from entering your critical area
- It effectively **attracts, collects and retains contamination** from the wheels of forklifts, pallet trucks, large trolleys and carts
- Large sizes available to ensure maximum decontamination of wheels
- Comes complete with two different edging options: heavy duty aluminium edging or a lower profile stainless steel option
- Coving and inlaid options available
- Periodic replacement or service contract available
- Masking available to hide contamination once on Dycem



We produce less permanent flooring solutions, should you need the flexibility to be able to move the flooring - visit www.dycem-cc.com/ productrange

or speak to one of our experts to dicuss the best option for you

# WITH DYCEM WITH DYCEM SATISFACTION IS GUARANTEED

There are two ways to begin specifying Dycem into your facility. Either contact us for a free site survey by one of our Contamination Control experts or send us your floorplans and we'll put together visuals to show you the areas that could greatly benefit from Dycem.

- On-site survey and demonstration to assess your contamination control needs.
- Provide samples and supporting literature with everything you need to know about Dycem products.
- A technical report identifying which Dycem product best suits your needs and operating budget.

- Full installation or installation training, dependent on your final choice of product.
- Cleaning demonstration ensuring your operatives understand the simple cleaning process and supply of recommended cleaning products.
- Comprehensive warranty and service options ensuring you are covered for the life cycle of your product.



### **Dycem** contamination control solutions used within **critical** and **controlled environments**:

- Attracts, collects and retains particle sizes from 0.1 micron to 100 micron
- Reduces cross contamination and bioburden
- Manufactured as an optically smooth and flexible surface enabling maximum contact between shoes and wheels
- Dycem CleanZone/WorkZone systems typically have a product life cycle of between 1-5 years (depending on environment and traffic conditions)

### **Case Study: Ulleval University Hospital Kitchen** Norway

Before Dycem, Ulleval used footbaths to help control contamination from entering the facilities, but it was decided that due to the expense of installation and maintenance of footbaths, another solution was needed. Dycem offered a comparably inexpensive, long-lasting, low maintenance solution that not only provided superior anti-microbial contamination control, but was a dry solution, thus improving health and safety within the kitchen environments.

### Call Dycem today for a **FREE** site survey

### DISCOVER HOW DYCEM CAN PROTECT YOUR BUSINESS

### **Dycem Ltd Europe**

Ashley Trading Estate Bristol BS2 9BB United Kingdom

Tel: +44 (0)117 955 9921 Fax: +44 (0)117 954 1194 uk@dycem.com







www.dycem-cc.com

"Dycem offered a comparably inexpensive long lasting, **low maintenance solution** that not only **provided superior antimicrobial contamination control**, but was a dry solution".

Egil Brevik Head Chef Ulleval University Hospital